



DOP: 3475-1224-063-000

Technical Details | Technische Daten

Manufacturing process | *Herstellungsart*
Frontside structure | *Oberseitengestaltung*
Color | *Farbgestaltung*
Pile material | *Material der Nutzschicht*
Primary backing | *Träger- / Grundgewebe*
Secondary backing | *Rückenausstattung*
Pile weight | *Poleinsatzgewicht*
Total weight | *Gesamtgewicht*
Pile height | *Polhöhe*
Total thickness | *Gesamtdicke*
Number of knots | *Noppenzahl*
Width | *Breite*

DIN ISO 2424 **tufted** | *getuftet* 1/10"
DIN ISO 2424 **Cut pile – saxony** | *Schnittpol Saxony Velours*
DIN ISO 2424 **Chromojet print** | *Chromojet Druck*
100 % Polyamid PA 6
DIN ISO 2424 **PES Woven** | *PES Gewebe*
DIN ISO 2424 **Action Back** | *Textilrücken*
DIN ISO 2424 approx. | ca. **1245 g/m²**
ISO 8543 approx. | ca. **2418 g/m²**
ISO 1766 approx. | ca. **6,0 mm**
ISO 1765 approx. | ca. **7,8 mm**
ISO 1763 approx. | ca. **237000 /m²**
DIN 3018 approx. | ca. **400 cm**

Functional properties | Funktionseigenschaften

Wear classification | *Beanspruchungsklasse* EN 1307:2019 **23/33**
Comfort rating | *Komfortklasse* EN 1307:2019 **LC 5**
Castor chair resistance | *Stuhlrolleneignung* EN 985: Prüfung A **Class A | Klasse A**

Physical properties | Bauphysikalische Eigenschaften

Fire rating | *Brandverhalten* DIN EN 13501-I **Cfl-s1***

*glued on massive mineral concrete | verklebt auf massiven mineralischen Untergründen

Fastnesses | Echtheiten

Colour fastness to light | *Lichtechtheit* EN ISO 105-B02:2013 **6-7**
Colour fastness to water | *Wasserechtheit* DIN EN ISO 105 E01:2013 **5**
Rubbing fastness dry/wet | *Reibechtheit trocken/nass* DIN EN ISO 105 X12:2002 **5/5**

The exporter of the products by this document, declares that, except were otherwise clearly indicated, these products are of preferential European community origin **HS/Tariff code:** 5703.2018 **MCI Carpets:** EORI number: NL854949434.



Rev.: 004/10.2023

These details are approximate. Complete specification details and associated certificates together with tolerances applying to the above can be provided upon request. We reserve the right to alter specifications without notice. Due to method of manufacture, perfect pattern and/or colour matching cannot be guaranteed. In cut pile carpet, shading/pile reversal might occur without affecting overall quality and suitability. Shading/pile reversal will not be considered as a manufacturing fault and will not affect the durability of the carpet.